## (12) International application published under the patent cooperation treaty (PCT)

## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 14 October 2004 (14.10.2004)

PCT

(10) International Publication Number WO 2004/088094 A2

(S1) International Patent Classification7:

FO1L

(21) International Application Number:

PCT/EP2004/003264

(22) International Filing Date: 26 March 2004 (26.03.2004)

(25) Filing Language:

English

(26) Publication Language:

10 2004 003 327.7

English

(30) Priority Data: 29 March 2003 (29.03.2003) 103 14 683.0 DE 14 May 2003 (14.05.2003) 103 23 665.1 DE 3 November 2003 (03.11.2003) 103 52 677.3 8 January 2004 (08.01.2004) DE 10 2004 001 343.8 DE 22 January 2004 (22.01.2004)

(71) Applicants (for all designated States except US): HIY-DRAULIK-RING GMBH [DE/DE]; Am Schlossfeld 5, 97828 Marktheidenfeld (DB). ENTEC CONSULTING GMBH [DE/DE]; Im Beil 7, 58675 Hemer (DE).

(71) Applicant and

(72) Inventor: BÖSL-FLIERL, Gerlinde [DE/DE]; Brunnenstrasse 62, 7661 Kaiserslautern (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FLIERL, Rudolf [DE/DE]; Brunnenstrasse 62, 67661 Kaiserslautern (DE). HANNIBAL, Wilhelm [DE/DE]; Im Beil 7, 58675 Hemer (DE). JUBELT, Michael [DE/DE]; Otto-Schuster-Strasse 49, 73760 Ostfildern (DE). KNECHT, Andreas [DE/DE]; Lustnauer Strasse 43, 72127 Kusterdingen (DE). WILD, Andreas [DE/DE]; Bettweg 17, 72669 Unterensingen

- (74) Agents: RICKER, Mathlas et al.; Jones Day, Prinzregentenstrasse 11, 80538 München (DB).
- (31) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (E4) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazene.

(\$4) Title: VARIABLE VALVE LIFT DEVICE FOR THE LIFT ADJUSTMENT OF GAS-EXCHANGE VALVES OF AN INTER-NAL COMBUSTION ENGINE

(57) Abstract: In order to produce a variable valve lift device for the lift adjustment of the gas-exchange valves of an internal combustion engine, by means of which with adjustment forces and holding forces, independently from whether said holding forces and adjustment forces are applied mechanically, hydraulically or electrically, with an adjustment of the valve lift being as costeffective as possible, and with maximum accuracy of the adjustment or control of the valve lift to be taken between the individual cylinders of a multi-cylinder internal combustion engine, and, moreover, the adjustment possibility of the valve lift of the valves of an internal combustion engine with several cylinders is obtained within smallest tolerances, it is suggested that a valve lift device (1) has a rotatable eccentric shaft (3), which consists of several eccentrics (4, 5) and whereby all possible contours of the eccentrics (4, 5) are positioned within a circle, which is formed by means of the external diameters of a bearing (6, 7) of the eccentric shaft (3).

BEST AVAILABLE COP